



	A	B	C	D	E	F
	ROW	SIDEWALK	LANDSCAPE STRIP	BIKE LANE	TRAVEL LANE	MEDIAN LANE
MAJOR ARTERIAL	104'	8'	N/A	6'	12' (UP TO 4)	14'
MINOR ARTERIAL	76'	5' RES 10-12' COM	6' RES TREE WELLS COM	6'	11' (UP TO 2)	12'
MAJOR COLLECTOR	74'	5' RES 10-12' COM	6' RES TREE WELLS COM	5'	11' (UP TO 2)	12'
MINOR COLLECTOR	56-6 6'	5' RES 10-12' COM	6' RES TREE WELLS COM	5' OR SHARED LANE	10' (UP TO 2)	10'
LOCAL	50'	5'	5'	SHARED LANE	SINGLE LANE	N/A

NOTES:

1. MINIMUM ASPHALT LIFT OF 1.5", MAXIMUM ASPHALT LIFT OF 3"
2. 5" MINIMUM ASPHALT THICKNESS FOR COLLECTOR AND ARTERIAL STREETS, 3" MINIMUM FOR LOCAL STREETS
3. MAXIMUM STREET GRADE DEPENDANT ON STREET TYPE, SEE McMINNVILLE MUNICIPAL CODE 17.53.101(L)(1)
4. CURB AND GUTTER BUILT TO McMINNVILLE STANDARD DETAIL NO. 6
5. MAJOR ARTERIAL STREETS MAY HAVE 2 OR 4 TRAVEL LANES
6. REFERENCE ADOPTED TRANSPORTATION SYSTEMS PLAN FOR OTHER REQUIREMENTS AND DETAILS
7. ALTERNATE UTILITY LOCATIONS CAN BE CONSIDERED AND APPROVED BY ENGINEERING. LOCATION OF MANHOLES SHOULD BE OUT OF THE TIRE PATH AND AVOID CONFLICTS WITH SURVEY MONUMENTS OR OTHER IMPROVEMENTS

**City of  
McMinnville**

DETAIL FOR  
TYPICAL STREET  
SECTION

DRAWN BY:

L.A.

DATE:

FEBRUARY 2025

DRAWING NO.

40